

ASHVALE™ & HOLKHAM RED / NATURAL CLAY PANTILES

The Ashvale clay pantile offers individuality in appearance created by hand finishing whilst retaining the economic and quality advantages associated with machine made pantiles, essential for today's market and the UK Climate.

The Holkham Barn tile is a hand finished clay pantile with a flatter and slightly wider profile than the Ashvale more typical of the traditional tile found in Norfolk. It has the appearance of a reclaimed barn tiles, but with all the advantages of availability, quality and price attributed to new tiles.

Colours Available

Restoration / Weathered	Red / Natural	Black Glazed
-------------------------	----------------------	--------------

Ashvale

Minimum roof pitch	30°
Batten spacing	270mm
Size of tile	335 x 240mm
Covering capacity	18.6 tiles per m ²
Cover width	200mm
Profile depth	50mm
Hanging length	315mm
Weight as laid	41.66kg per m ²
Weight per tile	2.24kg
Gross weight per pallet	0.89 tonnes
Quantity per pallet	375
Battens per m ²	3.7m
Batten size	50 x 25mm
Nail size/type of tiles	50 x 3.35mm alloy clout
Guarantee	30 years

Holkham

Minimum roof pitch	30°
Batten spacing	285mm
Size of tile	360 x 250mm
Covering capacity	16.7 tiles per m ²
Cover width	210mm
Profile depth	35mm
Hanging length	340mm
Weight as laid	41.75kg per m ²
Weight per tile	2.5kg
Gross weight per pallet	0.98 tonnes
Quantity per pallet	320
Battens per m ²	3.5m
Batten size	50 x 25mm
Nail size/type of tiles	50 x 3.35mm alloy clout
Guarantee	30 years



Suitability & Use

The Ashvale and Holkham barn clay pantiles can both be used on roofs pitched to 30° assuming they are fixed in accordance with the British Standard Code Of Practice for slating & tiling BS 5534: 2014.

However, if your pitch is lower than 30°, please contact us with details of your requirements and we can offer a clay pantile solution down to a pitch as low as 17.5° from our French collection. Both tiles are suitable for use in any part of the country, but indigenously pantiles are more commonly found in East Anglia and up the East coast of England.

Certification & Testing

All tiles comply with C E Marking to British and European Standard BS EN 1304, which legislates for externally tested and verified quality of roof tiles. The tiles are independently tested and verified quality of roof tiles. The tiles are independently tested to the following standards by Lucideon (approved by UKAS and the British Standards Institute):

- Determination of impermeability: BSEN 539-1:2005 Method 2 & BSEN 1304:2005
- Determination of flexural strength: BSEN 538:1994
- Determination of frost resistance: BSEN 539-2:2013

Copies of the latest test results, declaration of performance and CE marking are available as downloads from our website or please contact us and we will send them to you.