

## PANNE S BURNT RED CLAY PANTILE

A beautiful traditional clay tile designed to adorn and complement roofscapes in regions where the Old English Pantile has been the first choice for centuries.

### Colours Available

Natural Red	Rustic Red	<b>Burnt Red</b>
Satin Black	Slate	Old Vintage

### Technical Data

Quantity per pallet	420 tiles
Coverage	20.0 tiles per m <sup>2</sup>
Batten gauge*	275mm
Overall length	342mm
Overall width	232mm
Cover width	190mm
Headlap	64mm
Weight per tile	2.3kg
Weight per m <sup>2</sup> at maximum gauge	46.0kg
Minimum roof pitch	22.5°
Batten coverage per m <sup>2</sup>	3.63m
Batten sizes	38 x 25mm for rafter centres up to 450mm 50 x 25 mm for rafter centres up to 600mm
Tile nail	50 x 3.35mm aluminium clout head

### Fixing Specification

BS 5534 states that all interlocking tiles must be mechanically fixed. Use Edilians' roof tile fixing calculation service to ensure your roof is designed & installed in accordance with BS 5534.

### Manufacturing Standards

Edilians tiles fully comply with the requirements of BS EN 1304; the European Standard for clay tiles & fittings & are manufactured under a Quality Management system certified to comply with ISO 9001.



### Environmental Standards

All Edilians manufacturing sites are certified to Environmental Management System ISO 14001. In addition, Edilians complies with BES 6001: Responsible Sourcing. Edilians has a corporate policy for sustainable development, with environmental & social implementation key components of its overall performance. Strict standards are set for its manufacturing plants for emission, water & waste management. Responsible environmental management is important to Edilians by restoration of the landscape. Creating valuable wildlife habitats and recreation of heathland areas & forestry.

### Installation

All tiles, fittings & accessories should be installed in accordance with the recommendations given in BS 5534: the British Standard Code of practice for slating & tiling. Sitework should be carried out in accordance with BS 8000-6: the British Standard for workmanship on building sites. Contact Edilians Technical Support for projects where the rafter length exceeds 6 metres.

### 30 Year Guarantee

Edilians clay roof tiles are covered by a comprehensive 30-year guarantee of durability provided that they have been installed in accordance with BS 5534 & BS 8000-6.

\*Always check each batch of tiles delivered to site to determine the actual gauge, which may vary slightly due to drying and firing shrinkage during the manufacturing process.