



PANNE S SLATE CLAY PANTILE

A beautiful traditional clay tile designed to adorn and complement roofscapes in regions where the Old English Pantile has been the first choice for centuries.

Colours Available

Natural Red	Rustic Red	Burnt Red
Satin Black	Slate	Old Vintage

Technical Data

Quantity per pallet	420 tiles
Coverage	20.0 tiles per m ²
Batten gauge*	275mm
Overall length	342mm
Overall width	232mm
Cover width	190mm
Headlap	64mm
Weight per tile	2.3kg
Weight per m ² at maximum gauge	46.0kg
Minimum roof pitch	22.5°
Batten coverage per m ²	3.63m
Batten sizes	38 x 25mm for rafter centres up to 450mm 50 x 25 mm for rafter centres up to 600mm
Tile nail	50 x 3.35mm aluminium clout head

Fixing Specification

BS 5534 states that all interlocking tiles must be mechanically fixed. Use Edilians' roof tile fixing calculation service to ensure your roof is designed & installed in accordance with BS 5534.

Manufacturing Standards

Edilians tiles fully comply with the requirements of BS EN 1304; the European Standard for clay tiles & fittings & are manufactured under a Quality Management system certified to comply with ISO 9001.



Environmental Standards

All Edilians manufacturing sites are certified to Environmental Management System ISO 14001. In addition, Edilians complies with BES 6001: Responsible Sourcing. Edilians has a corporate policy for sustainable development, with environmental & social implementation key components of its overall performance. Strict standards are set for its manufacturing plants for emission, water & waste management. Responsible environmental management is important to Edilians by restoration of the landscape. Creating valuable wildlife habitats and recreation of heathland areas & forestry.

Installation

All tiles, fittings & accessories should be installed in accordance with the recommendations given in BS 5534: the British Standard Code of practice for slating & tiling. Sitework should be carried out in accordance with BS 8000-6: the British Standard for workmanship on building sites. Contact Edilians Technical Support for projects where the rafter length exceeds 6 metres.

30 Year Guarantee

Edilians clay roof tiles are covered by a comprehensive 30-year guarantee of durability provided that they have been installed in accordance with BS 5534 & BS 8000-6.

*Always check each batch of tiles delivered to site to determine the actual gauge, which may vary slightly due to drying and firing shrinkage during the manufacturing process.



ETHICALLY SOURCED



EXPERTLY CRAFTED



BEAUTIFULLY FINISHED



TRUSTED EXPERTS