

PHALEMPIN VOLCANO TRADITIONAL PLAIN CLAY TILE

The 17 x 27 traditional clay plain tile is produced at Phalempin in the Normandy region of France.

The Phalempin range offers a variety of mellow mature colour tones with some pre-mixed blend options a sympathetic indigenous solution at an affordable price.

Colours Available

Amber Vintage	Weathered Millenium	Rustic Red Volcano Val de Seine		
Technical Data				
Quantity per pal	let	1088 tiles	1088 tiles	
Coverage at 100	mm gauge	60.0 tiles per m²	60.0 tiles per m ²	
Batten gauge (va	ariable)	100mm roof 115mm ver	100mm roof 115mm vertical	
Overall length		270mm	270mm	
Overall width		170mm	170mm	
Cover width		170mm	170mm	
Minimum headla	ap at 100mm gaug	e 70mm	70mm	
Weight per tile		1.1kg	1.1kg	
Weight per m² at maximum gauge		65.0kg	65.0kg	
Batten coverage m² at 100mm gauge		ge 10.0m	10.0m	
Batten sizes		38 x 25mm for rafter ce up to 600mm	38 x 25mm for rafter centres up to 600mm	
Tile nail		38/40 x 2.65mm alumir clout head	38/40 x 2.65mm aluminium clout head	

*Except Millenium Mix; minimum pitch: 350

Technical Services

Fixing Specification

BS 5534 states that all interlocking tiles must be mechanically fixed. Use Edilians' roof tile fixing calculation service to ensure your roof is designed & installed in accordance with BS 5534.

Manufacturing Standards

Edilians tiles fully comply with the requirements of BS EN 1304; the European Standard for clay tiles & fittings & are manufactured under a Quality Management system certified to comply with ISO 9001.



Environmental Standards

All Edilians manufacturing sites are certified to Environmental Management System ISO 14001. In addition, Edilians complies with BES 6001: Responsible Sourcing. Edilians has a corporate policy for sustainable development, with environmental & social implementation key components of its overall performance. Strict standards are set for its manufacturing plants for emission, water & waste management. Responsible environmental management is important to Edilians by restoration of the landscape. Creating valuable wildlife habitats and recreation of heathland areas & forestry.

Installation

All tiles, fittings & accessories should be installed in accordance with the recommendations given in BS 5534: the British Standard Code of practice for slating & tiling. Sitework should be carried out in accordance with BS 8000-6: the British Standard for workmanship on building sites. Contact Edilians Technical Support for projects where the rafter length exceeds 6 metres.

30 Year Guarantee

6

BEAUTIFULLY FINISHED

Edilians clay roof tiles are covered by a comprehensive 30-year guarantee of durability provided that they have been installed in accordance with BS 5534 & BS 8000-6.



EXPERTLY CRAFTED



🕀 lifestiles.co.uk

TRUSTED EXPERTS